SUPERIOR CLEANING





Fast drying cyclus



Large opening



OPTIONS

- ☑ Easy to use timer
- ☑ Electrical, Gas and Steam heating
- ☑ Large door opening for easy loading and unloading (Ø57cm)
- ☑ Axial airflow
- ☑ Large lint filter

□ Stainless steel drum □ Coin operated version □ Reversing drum

- □ Residual moisture control:
 - lower energy and utility costs
 - lower linen replacement costs







SUPERIOR CLEANING

CAPACITY	Capacity	ke	1 24
CALACITI	Drum volume		491
	Drum diameter		Ø 838
	Didili dialiletei	"""	000
AIRFLOW	50 Hz	1/	283
AIRFLOW	60 Hz		330
	60 HZ	U.	330
DDVING AVEDAGE	Caallastina	- 6	
DRYING AVERAGE	Gas Heating		444
	Electric Heating	g/mii	399
	_		
MOTOR	Fan		0,375
	Drive	KV	0,375
GAS HEATING	Energy		29,9
	Energy	kBTU/I	
	Gas connection	NP	1/2"
STEAM HEATING	High presure 6,9 bar	Kv	(#)
		kBTU/I	(4)
	Steam connection	NP	T (ii)
ELECTRICAL HEATING	Energy	kV	/ 27
	9,		
EXHAUST		Ø/mn	203
DIMENSIONS	HxDxW	mn	1695x876x1362
	Net Weight		197
	5		
TRANSPORT DATA	Gross Weight	ko	216
	Packing HxWxD		1829x902x1489
	Side TD-490R	Side TD-490R Electric Side TD-490R Gas	
	857.25 mm	774.7 mm 876 mm Top TD-490R Gas	
		41.17 mm (NON CE)	

